

Professional pneumatic stainless steel foamer

High-quality 10 litre foaming unit for professional cleaning, detailing and industrial wash-down applications.

Typical Applications Food Processing • Dairy • Meat Processing • Industrial Cleaning • Vehicle Wash • Sanitation • Workshops • Agriculture • Construction Equipment • Fleet Cleaning



SCG10X

10 litre stainless steel foamer - PED 2014/68/EU

A professional pneumatic foamer designed for demanding cleaning workflows. The unit is filled to approximately three quarters of its capacity with liquid and charged with compressed air up to 8 bar.

Use note: continuous connection to the compressed air network is required.

10 L TANK CAPACITY	8 bar MAX PRESSURE	10 m HOSE LENGTH
AISI 316L STAINLESS STEEL	10.5 kg NET WEIGHT	PED 2014/68/EU

KEY BENEFITS

Foam & Spray in One Unit One machine, two applications. The SCG10X can be used both as a professional foam generator and as a pneumatic sprayer by simply replacing the foam head with the supplied spray nozzle.	
Built for professional foam application Pneumatic operation and a 10 m hose support efficient work around vehicles, equipment and wash bays.	Stainless steel construction AISI 316 stainless steel construction for durable professional use.
Ready-to-use delivery set Supplied with LC-1 stainless steel lance, spray nozzle, nozzle protection and foam head.	Italian manufacturing & PED compliance Manufactured in Italy in compliance with the Pressure Equipment Directive (PED) 2014/68/EU. The equipment is manufactured under the surveillance of TÜV Austria Italia in accordance with Accredia requirements.

TECHNICAL DATA

Feature	SCG10X
HS Code	8424.30.10
Material	AISI 316L Stainless Steel
Operation	Pneumatic
Capacity	10 litres
Maximum liquid capacity	9 litres
Spray lance length	600 mm
Hose length	10 m
Max pressure	8 bar
Net Weight	10.5 kg
Gross Weight	11.5 kg
Packing Dimensions	29 x 36 x H81 cm

STANDARD EQUIPMENT

- 10 m hose
- LC-1 stainless steel lance
- Spray nozzle
- Nozzle protection

- Foam head
- Tank with automatic level indicator
- Safety valve set at 8 bar

Optional Accessories

The SCG10X can be configured with optional accessories to meet different cleaning applications.

 <p>TSCG2 Super Foam Head Produces a thicker and more stable foam for demanding cleaning applications.</p>	 <p>RGN Pressure Regulator Allows precise adjustment of the working pressure according to the application.</p>
--	--

Other accessories and spare parts available upon request.

OPERATION

Fill the tank with liquid to approximately three quarters of its capacity and charge it with compressed air up to a maximum pressure of 8 bar. Continuous connection to the compressed air network is required.

SAFETY


Do not use solvents, explosive or corrosive liquids. Only liquids with a flash point above 65 °C may be used.

COMPLIANCE & ORIGIN

Manufactured in Italy in compliance with the Pressure Equipment Directive (PED) 2014/68/EU. The equipment is manufactured under the surveillance of TÜV Austria Italia in accordance with Accredia requirements.

PRODUCT PAGES

Quick access to model-specific technical information.



MANUFACTURER

Lanzoni Techclean di Lanzoni A. & C. snc

Via al Palazzo 10, 42030 Vezzano sul Crostolo (RE), Italy

+39 0522 606311

lanzoni@lanzonline.com

www.lanzonline.com

VAT No.: IT00713670354