

Professional pneumatic painted carbon steel foamer

High-quality 24 litre foaming unit for professional cleaning, detailing and industrial wash-down applications.

Typical Applications Industrial Cleaning • Vehicle Wash • Workshops • Agriculture • Construction Equipment • Fleet Cleaning



SCG25

24 litre painted carbon steel foamer - PED 2014/68/EU

A professional pneumatic foamer designed for demanding cleaning workflows. The unit is filled to approximately three quarters of its capacity with liquid and charged with compressed air up to 8 bar.

Use note: continuous connection to the compressed air network is required.

24 L TANK CAPACITY	8 bar MAX PRESSURE	10 m HOSE LENGTH
Painted carbon steel CARBON STEEL	13 kg NET WEIGHT	PED 2014/68/EU

KEY BENEFITS

<p>Foam & Spray in One Unit One machine, two applications. The SCG25 can be used both as a professional foam generator and as a pneumatic sprayer by simply replacing the foam head with the supplied spray nozzle.</p>	
<p>Built for professional foam application Pneumatic operation and a 10 m hose support efficient work around vehicles, equipment and wash bays.</p>	<p>Painted carbon steel construction Painted carbon steel construction for durable professional use.</p>
<p>Ready-to-use delivery set Supplied with LC-2 stainless steel lance, spray nozzle, nozzle protection and foam head.</p>	<p>Italian manufacturing & PED compliance Manufactured in Italy in compliance with the Pressure Equipment Directive (PED) 2014/68/EU. The equipment is manufactured under the surveillance of TÜV Austria Italia in accordance with Accredia requirements.</p>

TECHNICAL DATA

Feature	SCG25
HS Code	8424.30.10
Material	Painted carbon steel
Operation	Pneumatic
Capacity	24 litres
Maximum liquid capacity	19 litres
Spray lance length	750 mm
Hose length	10 m
Max pressure	8 bar
Net Weight	13 kg
Gross Weight	14 kg
Packing Dimensions	29 × 36 × H81 cm

STANDARD EQUIPMENT

- 10 m hose
- LC-2 stainless steel lance
- Spray nozzle
- Nozzle protection

- Foam head
- Tank with automatic level indicator
- Safety valve set at 8 bar

Optional Accessories

The SCG25 can be configured with optional accessories to meet different cleaning applications.

 <p>TSCG2 Super Foam Head Produces a thicker and more stable foam for demanding cleaning applications.</p>	 <p>RGN Pressure Regulator Allows precise adjustment of the working pressure according to the application.</p>
--	--

Other accessories and spare parts available upon request.

OPERATION

Fill the tank with liquid to approximately three quarters of its capacity and charge it with compressed air up to a maximum pressure of 8 bar. Continuous connection to the compressed air network is required.

SAFETY

Do not use solvents, explosive or corrosive liquids. Only liquids with a flash point above 65 °C may be used.

COMPLIANCE & ORIGIN

Manufactured in Italy in compliance with the Pressure Equipment Directive (PED) 2014/68/EU. The equipment is manufactured under the surveillance of TÜV Austria Italia in accordance with Accredia requirements.

PRODUCT PAGES

Quick access to model-specific technical information.



MANUFACTURER

Lanzoni Techclean di Lanzoni A. & C. snc

Via al Palazzo 10, 42030 Vezzano sul Crostolo (RE), Italy

+39 0522 606311

lanzoni@lanzonline.com

www.lanzonline.com

VAT No.: IT00713670354